

INDUSTRIAL HOSE - MULTI-PURPOSE



PREMO FLEX® 20 METRE HOSE COILS



Premo Flex® is the perfect choice for multiple applications requiring a highly flexible, cost effective hose with maximum resistance to petroleum oils, kerosene and fuel oil [up to 49°C].

Premo Flex® is suitable for air and water applications, offering excellent weather and ozone resistance, and is non-conductive at 1000 volts D.C. Premo Flex® can also be used for transferring gasoline or diesel fuels [but is not suitable as a fuel line hose].

PREMO FLEX® 20 METRE HOSE COILS

- > Available in 4 popular sizes including 5/16", 3/8", 1/2" & 3/4"
- > Offered in a convenient length
- > Retail friendly packaging

AIR & MULTI PURPOSE HOSE									
Premo Flex® Spec. 3205R							Prod. Group: 1180A		
Nom. I.D. [In.]	Nom. I.D. [mm]	Nom. O.D. [In.]	Nom. O.D. [mm]	Wt per m. [kg]	Package	Standard Length [m.]	Product Number	Product Description	Unit of Measure
5/16	7.9	0.56	14.2	0.15	Coil	20	3205-0020C	PREMOFLEX 250 5/16" 20MTR	M
3/8	9.5	0.66	16.8	0.20	Coil	20	3205-0025C	PREMOFLEX 250 3/8" 20MTR	M
1/2	12.7	0.85	21.6	0.33	Coil	20	3205-0030C	PREMOFLEX 250 1/2" 20MTR	M
3/4	19.0	1.15	29.2	0.52	Coil	20	3205-0040C	PREMOFLEX 250 3/4" 20MTR	M

PREMO FLEX® MULTI PURPOSE HOSE COVERS A DIVERSE ARRAY OF APPLICATIONS

Suitable to any end market using or dealing with the following:

- > Air tools/compressors
- > Air supplies for applications requiring backpressure
- > Water discharge applications
- > Suitable for transfer of gasoline and diesel fuel [Note: not to be used as fuel line]
- > Agriculture – Ag sprays, herbicides/pesticides
- > Suitable for supplied air respirator hose [Tube meets former military air breathing spec for hydrocarbon off-gassing]

• Factories • Quarries • Construction • Agriculture • Forestry • Firefighting / Air breathing • Mining • Aluminium Plants

COMPETITIVE COMPARISON MATRIX

	GATES PREMO FLEX®	VEYANCE ORTAC	PARKER MPT II	EATON SHOCK-SAFE
TUBE STANDARD	RMA [Class A]	RMA [Class A]	RMA [Class A]	RMA [Class A]
COVER STANDARD	RMA [Class B]	RMA [Class A]	RMA [Class C]	RMA [Class C]
REINFORCEMENT	Spiral	Spiral	Spiral	Braid
PRESSURE	250	250	250	275
TEMP [°C]	100	88	100	82
NON-CONDUCTIVE	YES	YES	YES	YES
COUPLINGS	GLX	NO	YES	YES
DESIGN FACTOR	4:1	4:1	4:1	4:1

GATES AUSTRALIA PTY LTD

1-15 Hydrive Close, Dandenong South, Victoria, 3175
 PH: +61 3 9797 9666 FAX: +61 3 9797 9600
gatesaustralia.com.au

For application information, please scan here to
 visit the Gates website at: gatesaustralia.com.au

